

Master-Core Basic & Master-Core Professional

Developed by Prof. Istvan Urban

The Bone Management® Master-Core Basic and Professional Systems are used for the simple and safe extraction of bone cylinders in the context of bone augmentation. For this purpose, the systems contain trephines with different lengths and diameters. Due to the different lengths, the trephines have an automatic depth stop, which ensures the protection of anatomical structures and thus allows for a particularly safe and controlled bone extraction. In addition, depth markings on the trephines' working parts enable additional depth control during the extraction. The black coating of the trephines allows for glare-free work and the optimal visibility of the depth markings.



At a glance















- Simple and safe extraction of bone cylinders
- Optimal protection of anatomical structures thanks to depth-limited trephines
- Depth markings on the trephines for additional depth control
- Extraction of bone cylinders of different diameters and lengths
- Black coating on the trephines for glare-free work

Our sales force would be pleased to answer your questions: +49 2131 2012-303

Heisinger since 1888

	Fig.	Shank	Size	Inner-/Outer-Ø/Length [mm]	recommended / max. Speed [rpm]	Pieces / Kit	Amount
	BMCBA	-	-	-	-	-	
	DV229	204	050	Ø 5,0/6,0, -	300-500 / 800	1	
	DV229	204	070	Ø 7,0/8,0, -	300-500 / 800	1	
	229IU	206	603	Ø 5,0/6,0, L3	300-500 / 800	1	
	229IU	206	604	Ø 5,0/6,0, L4	300-500 / 800	1	
	229IU	206	605	Ø 5,0/6,0, L5	300-500 / 800	1	
	229IU	206	606	Ø 5,0/6,0, L6	300-500 / 800	1	
	229IU	206	607	Ø 5,0/6,0, L7	300-500 / 800	1	
	229IU	206	803	Ø 7,0/8,0, L3	300-500 / 800	1	
	229IU	206	804	Ø 7,0/8,0, L4	300-500 / 800	1	
	229IU	206	805	Ø 7,0/8,0, L5	300-500 / 800	1	
	229IU	206	806	Ø 7,0/8,0, L6	300-500 / 800	1	
	229IU	206	807	Ø 7,0/8,0, L7	300-500 / 800	1	
	BV025	205	-	Ø - / -, L25,5	/ 15.000	1	

Additionally included in the Master-Core Professional system:

	BMCPR	-	-	-	-	-	
	DV229	204	040	Ø 4,0/5,0, -	300-500 / 800	1	
	DV229	204	060	Ø 6,0/7,0, -	300-500 / 800	1	
	229IU	206	503	Ø 4,0/5,0, L3	300-500 / 800	1	
	229IU	206	504	Ø 4,0/5,0, L4	300-500 / 800	1	
	229IU	206	505	Ø 4,0/5,0, L5	300-500 / 800	1	
	229IU	206	506	Ø 4,0/5,0, L6	300-500 / 800	1	
	229IU	206	507	Ø 4,0/5,0, L7	300-500 / 800	1	
	229IU	206	703	Ø 6,0/7,0, L3	300-500 / 800	1	
	229IU	206	704	Ø 6,0/7,0, L4	300-500 / 800	1	
	229IU	206	705	Ø 6,0/7,0, L5	300-500 / 800	1	
	229IU	206	706	Ø 6,0/7,0, L6	300-500 / 800	1	
	229IU	206	707	Ø 6,0/7,0, L7	300-500 / 800	1	
	BV024	205	-	Ø - / -, L23,5	/ 15.000	1	

* excl. VAT. CE 0044

Hager & Meisinger GmbH

Hanemannstr. 10 • 41468 Neuss • Germany
 Phone: +49 2131 2012-0 • Fax: +49 2131 2012-222
 info@meisinger.de • www.meisinger.de

Meisinger USA, L.L.C.

10200 E. Easter Avenue • Centennial, Colorado 80112 • USA
 Phone: +1 (303) 268-5400 • Fax: +1 (303) 268-5407
 Toll free: +1 (866) 634-7464
 info@meisingerusa.com • www.meisingerusa.com

Your delivery address:

